NSN 5905-00-407-1647

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-407-1647

Electrical Resistance: 16.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.005 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.002 cubic inches Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Boddy Diameter: 0.105 inches Boddy Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.005 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.005 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end
0.002 cubic inches Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A001a0