NSN 5905-00-407-2505

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-407-2505 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.656 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.469 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Tab **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

N/a

Shelf Life:

NSN 5905-00-407-2505

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0