## NSN 5905-00-409-0472

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-409-0472

| Section Quantity:   |
|---|
| 3   |
| Body Style:   |
| Cylindrical servo mounted                                 |
| Reliability Indicator:                                    |
| Not established   |
| Pilot Diameter:   |
| 0.5000 inches   |
| Pilot Length:   |
| 0.0620 inches   |
| Undercut Diameter:  |
| 0.719 inches  |
| Undercut Width:   |
| 0.0620 inches   |
| Body Diameter:  |
| 0.750 inches  |
| Shaft Diameter:   |
| 0.125 inches  |
| Shaft Length:   |
| 0.500 inches  |
| Body Length:  |
| 1.750 inches  |
| Mounting Lip Diameter:                                    |
| 0.75000 inches  |
| Mounting Lip Depth:                                       |
| 0.06200 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Effective Electrical Rotation In Deg Angular Rotation:    |
| 360.0   |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Clamp ring  |
| Rotary Actuator Travel In Angular Deg:                    |
| 360.0   |
| Actuator Travel Control Feature:                          |
| Continuous motion   |
| Terminal Type And Quantity:                               |

12 wire lead

## NSN 5905-00-409-0472

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |

A002a0