

View Online at <https://aerobasegroup.com/nsn/5905-00-409-8367>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

2.031 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Body Length:

1.312 inches

Mounting Lip Diameter:

Between 1.9900 inches and 2.0050 inches

Mounting Lip Depth:

Between 0.0880 inches and 0.0980 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Mechanical Backlash In Deg Angular Rotation:

0.1

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Flange

Electrical Resistance Per Section:

80.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

90.0 single section and 90.0 single section and 90.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.35/+0.35 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section absolute conformity

Fixed Tap Quantity Per Section:

3 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section 360 degrees sine-cosine

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0