NSN 5905-00-410-2770

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-410-2770

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
0.938 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
0.875 inches
Body Length:
0.688 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
265.0
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
160.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
4.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
285.0
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Posistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-410-2770

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0