NSN 5905-00-410-2771

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-410-2771 **Section Quantity: Body Style:** Cylindrical bushing mounted **Body Diameter:** 0.938 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 0.688 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:**

Nonmetallic shaft **Electrical Resistance Per Section:** 4.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 285.0 **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section

NSN 5905-00-410-2771

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0