## NSN 5905-00-410-2774

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-410-2774 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.938 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 0.688 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Features Provided:** 

Nonmetallic shaft

**Electrical Resistance Per Section:** 

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

285.0

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

## NSN 5905-00-410-2774

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: -Demilitarization: No

Fiig: A002a0