

View Online at <https://aerobasegroup.com/nsn/5905-00-410-6404>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Pilot Diameter:

Between 1.31100 inches and 1.31200 inches

Pilot Length:

Between 0.05700 inches and 0.06700 inches

Undercut Diameter:

1.3125 inches

Undercut Width:

0.05700 inches

Body Diameter:

Between 1.420 inches and 1.450 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

Between 0.594 inches and 0.655 inches

Body Length:

1.539 inches

Mounting Lip Diameter:

Between 1.42000 inches and 1.45000 inches

Mounting Lip Depth:

Between 0.08800 inches and 0.08900 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

323.9

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

3.500 percent, rated amperes c and better industrial clears

Function Conformity Tolerance Per Section:

-0.40/+0.40 2nd section

Power Dissipation Rating Per Section In Watts:

10.0 7th secondary pattern

Function Conformity Per Section:

All sections absolute conformity

Fixed Tap Quantity Per Section:

1 1st section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 2nd section

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0