## NSN 5905-00-410-7405

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-410-7405

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular   |
| Terminal Length:  |
| 0.172 inches  |
| Shaft Diameter:   |
| 0.075 inches  |
| Shaft Length:   |
| 0.080 inches  |
| Body Length:  |
| 0.420 inches  |
| Body Width:   |
| 0.190 inches  |
| Body Height:  |
| 0.375 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Effective Electrical Rotation In Deg Angular Rotation:                      |
| Between 5400.0 and 10800.0  |
| Center To Center Distance Between Terminals:                                |
| 0.200 inches  |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Features Provided:  |
| Nonmetallic shaft   |
| Electrical Resistance Per Section:  |
| 100.000 ohms single section   |
| Rotary Actuator Travel In Angular Deg:                                      |
| Between 5400.0 and 10800.0  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.100 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -250.0 to 250.0 single section  |

0.5 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-00-410-7405

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| <b>Resistance Tolerar</b> | nce Per Section | n In Percent: |
|---------------------------|-----------------|---------------|
|---------------------------|-----------------|---------------|

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

81349-milr22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-22097/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0