## NSN 5905-00-410-7483

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-410-7483 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.390 inches **Undercut Diameter:** 1.3125 inches **Undercut Width:** 0.0630 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.460 inches **Body Length:** 0.930 inches **Overall Diameter:** 1.837 inches **Mounting Lip Diameter: Effective Electrical Rotation In Deg Angular Rotation:** 

1.4370 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft 360.0 **Maximum Starting Torque:** 0.12 inch-ounces **Maximum Running Torque:** 0.12 inch-ounces

## NSN 5905-00-410-7483

Precision Wire Wound Variable Resistor - Page 2 of 3



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 single section and 360.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.40/+0.40 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-600.0/+600.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
2 single section
Tap Location Tolerance Per Section:
-3.0/+3.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5905-00-410-7483

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0