NSN 5905-00-411-1954

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-411-1954 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6750 inches Pilot Length: 0.0570 inches **Overall Length:** 1.911 inches **Undercut Diameter:** 0.675 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.188 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.313 inches **Body Length:** 1.036 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0570 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:**

0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

NSN 5905-00-411-1954

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
100.00 inch-ounces
Shaft End Play:
0.002 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.062 inches
Shaft Radial Play:
0.005 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.125/+0.125 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-411-1954

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0