NSN 5905-00-411-1961

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-411-1961

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0610 inches
Overall Length:
1.912 inches
Undercut Diameter:
1.870 inches
Undercut Width:
0.0780 inches
Body Diameter:
2.109 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
0.974 inches
Overall Diameter:
2.594 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0930 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:

0.50 inch-ounces

NSN 5905-00-411-1961

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.001 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.80/+0.80 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 7th secondary quality
Function Conformity Per Section:
Single section terminal base linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:

N/a

NSN 5905-00-411-1961

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •			
ın	1+	<i>(</i>)+	Measure	•

--

Demilitarization:

No

Fiig:

A002a0