Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-411-3609

### Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.797 inches

#### **Terminal Length:**

6.000 inches

#### **Overall Height:**

0.500 inches

#### **Overall Width:**

0.220 inches

#### Mounting Slot Width:

0.093 inches

#### Shaft Diameter:

0.083 inches

# Shaft Length:

0.250 inches

# Body Length:

0.500 inches

#### Body Width:

0.220 inches

#### **Body Height:**

0.500 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

### Maximum Starting Torque:

5.00 inch-ounces

# Lateral Distance Between Mounting Hole Centers:

0.520 inches

# Screw Thread Diameter:

0.190 inches

# Screw Thread Series Designator:

Unf

#### Screw Thready Qty Per Inch (tpi):

32.0

2

N/a

---

No Fiig:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Standard bushing and unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 200.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: Unit Of Measure: **Demilitarization:** A002a0