Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-411-3610

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# Reliability Indicator:

Not established

# **Overall Length:**

0.797 inches

# **Overall Height:**

0.500 inches

#### **Overall Width:**

0.220 inches

# Mounting Slot Width:

0.093 inches

#### Shaft Diameter:

0.083 inches

# Shaft Length:

0.250 inches

# Body Length:

0.500 inches

# Body Width:

0.220 inches

# Body Height:

0.500 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

9000.0

# Maximum Starting Torque:

5.00 inch-ounces

# Lateral Distance Between Mounting Hole Centers:

0.520 inches

# Screw Thread Diameter:

0.190 inches

# **Screw Thread Series Designator:**

Unf

# Screw Thready Qty Per Inch (tpi):

32.0

# **Mounting Facility Quantity:**

2



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0