## NSN 5905-00-411-4830

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-411-4830

| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:   |
|---|
| Electrical Resistance: 6.190 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:   |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+170.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+170.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.155 inches Body Length: 0.350 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:  |
| Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.155 inches  Body Length: 0.350 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:   |
| Style Designator:   |
| Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.155 inches  Body Length:  0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  |
| Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.155 inches  Body Length: 0.350 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  |
| Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.155 inches  Body Length:  0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:   |
| Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.155 inches  Body Length:  0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  |
| 0.001  Body Diameter: 0.155 inches  Body Length: 0.350 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:   |
| Body Diameter:  0.155 inches  Body Length: 0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  |
| 0.155 inches  Body Length: 0.350 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:   |
| Body Length:  0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:   |
| 0.350 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:   |
| Power Dissipation Rating In Watts:  0.125 free air  Style Designator:   |
| 0.125 free air  Style Designator:   |
| 0.125 free air  Style Designator:  Avial terminal cash and  |
|   |
| Avial terminal each and   |
| Axial terminal each end   |
| Test Data Document:   |
| 94756-443-0969-023 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,   |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |