NSN 5905-00-412-0854

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-412-0854 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.969 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.438 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

2.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

NSN 5905-00-412-0854

Unit Of Measure:

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 4.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a