NSN 5905-00-412-1263

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-412-1263

| Section Quantity: |
|---|
| 1 |
| |
| Body Style: Cylindrical |
| Reliability Indicator: |
| Not established |
| |
| Overall Length: 0.688 inches |
| Terminal Length: |
| 0.500 inches |
| Body Diameter: |
| 0.312 inches |
| Body Length: |
| 0.188 inches |
| Overall Diameter: |
| 0.312 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 280.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0 to 5.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |

A single section

NSN 5905-00-412-1263

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0