NSN 5905-00-412-1264

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-412-1264 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.875 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.063 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 2.250 inches **Overall Diameter:** 2.063 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:**

1.20 inch-ounces **Maximum Running Torque:**

0.80 inch-ounces

NSN 5905-00-412-1264

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section
125.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts:
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section:
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature:
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section:
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Precious Material And Location:
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Precious Material And Location: Terminals gold
Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Precious Material And Location: Terminals gold Precious Material:

NSN 5905-00-412-1264

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0