NSN 5905-00-412-3573

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-412-3573

| Electrical Resistance: 100.000 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -66.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Resilability Indicator: Not established Body Dlameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 inches Power Dissipation Rating In Watts: 1.000 rece air Style Designator: Radial terminal each end Test Data Document: 24930-9310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig: A001a0 | Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|---|
| Resistance Tolerance in Percent: -1.0004-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: | -20.0/+20.0 |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.01 -65.01-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating in Watts: 1.000 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: | Electrical Resistance: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 100.000 kilohms |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inciosure Method: Encapsulated Terminal Type: Wire lead Reglability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | Resistance Tolerance In Percent: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 fee air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig: | Ambient Tempurature In Deg Celsius At Full Rated Power: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 ree air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | 25.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-9310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-9310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig: | 150.0 |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | -65.0/+125.0 |
| Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Inclosure Method: |
| Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Encapsulated |
| Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Terminal Type: |
| Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Wire lead |
| Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Reliability Indicator: |
| 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Not established |
| Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Body Diameter: |
| 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 0.375 inches |
| Power Dissipation Rating In Watts: 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Body Length: |
| 1.000 free air Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 1.000 inches |
| Style Designator: Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Power Dissipation Rating In Watts: |
| Radial terminal each end Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 1.000 free air |
| Test Data Document: 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Style Designator: |
| 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Radial terminal each end |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Test Data Document: |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 24930-g310027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| N/a Unit Of Measure: Demilitarization: No Fiig: | excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| | No |
| A001a0 | Fiig: |
| | A001a0 |
| | |