Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-412-3655

Saction	Quantity:
Section	Quantity.

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

**Overall Length:** 

- 0.625 inches
- Terminal Length:

0.250 inches

Body Diameter:

0.500 inches

Body Length:

0.375 inches

Actuator Type:

#### Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

360.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Terminal

### Center To Center Distance Between Terminal Rows:

0.100 inches

**Electrical Resistance Per Section:** 

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

360.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

### Actuator Travel Control Feature:

Continuous motion



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0