Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-412-3656

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.500 inches

#### **Body Length:**

0.215 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

320.0

#### **Terminal Location:**

.....

# Rear end

Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

200.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

320.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0 to 400.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

#### **Actuator Travel Control Feature:**

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0