NSN 5905-00-412-3995

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-412-3995 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0630 inches **Overall Length:** 1.442 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.2498 inches **Shaft Length:** 0.437 inches **Body Length:** 1.000 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Shaft End Play:

0.0015 inches

NSN 5905-00-412-3995

Shaft Runout: 0.001 inches Lateral Runout:

Precision Nonwire Wound Variable Resistor - Page 2 of 3



0.001 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.003 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
4.5 free air single section
Function Conformity Per Section:
Single section absolute conformity
·
Single section absolute conformity
Single section absolute conformity Fixed Tap Quantity Per Section:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch Tap Location From Ccw Terminal Per Section In Ohms:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch Tap Location From Ccw Terminal Per Section In Ohms: 1250.0 single section
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch Tap Location From Ccw Terminal Per Section In Ohms: 1250.0 single section Function Characteristic Per Section:
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch Tap Location From Ccw Terminal Per Section In Ohms: 1250.0 single section Function Characteristic Per Section: Single section 360 degrees sine-cosine
Single section absolute conformity Fixed Tap Quantity Per Section: 1 single section Tap Location Tolerance Per Section: -2.0/+2.0 ohms single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Clutch Tap Location From Ccw Terminal Per Section In Ohms: 1250.0 single section Function Characteristic Per Section: Single section 360 degrees sine-cosine Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

NSN 5905-00-412-3995

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0