NSN 5905-00-412-4041

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-412-4041

1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.500 inches
Overall Height:
0.406 inches
Overall Width:
0.190 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.250 inches
Body Length:
1.250 inches
Body Width:
0.266 inches
Body Height:
0.312 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6120.0 and 9720.0
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.240 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0

NSN 5905-00-412-4041

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Standard bushing and unthreaded hole
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.120 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0