Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-413-1007

### Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# Reliability Indicator:

Not established

### **Overall Length:**

0.455 inches

#### **Terminal Length:**

0.188 inches

**Overall Height:** 

#### 0.375 inches

**Overall Width:** 

#### 0.423 inches

Mounting Hole Diameter:

### 0.075 inches

Shaft Diameter:

0.093 inches

### Shaft Length:

0.080 inches

### Body Length:

0.375 inches

#### **Body Width:**

0.235 inches

### Body Height:

0.375 inches

#### Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Center To Center Distance Between Terminals:

0.200 inches

### Lateral Distance Between Mounting Hole Centers:

0.375 inches

### **Mounting Facility Quantity:**

2

## **Terminal Location:**

Left adjacent side single row

## **Mounting Method:**

Terminal and unthreaded hole

### **Electrical Resistance Per Section:**

500.000 ohms single section



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0