Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-415-5410

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
Between 0.172 inches and 0.202 inches
Shaft Diameter:
Between 0.088 inches and 0.098 inches
Shaft Length:
Between 0.075 inches and 0.085 inches
Body Length:
Between 0.397 inches and 0.413 inches
Body Width:
Between 0.180 inches and 0.200 inches
Body Height:
Between 0.370 inches and 0.380 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6480.0 and 10080.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Humidity proof
Cubic Measure:
0.029 cubic inches
0.029 cubic inches

NSN 5905-00-415-5410

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 6480.0 and 10080.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 5.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Sealed to permit cleaning in common solvents **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0