NSN 5905-00-416-3522 Thermal Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-416-3522 |
|---|
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.600 inches |
| Body Outside Diameter: |
| 0.215 inches |
| Terminal Diameter: |
| 0.250 inches |
| Maximum Power Dissipation Rating: |
| 250.00 milliwatts |
| Ambient Tempurature At Full Rated Power: |
| 25.0 degrees celsius |
| Maximum Operating Temp: |
| 125.0 degrees celsius |
| Thermal Time Constant In Seconds: |
| 60.0 |
| Power Dissipation Constant In Milliwatts Per Deg Celsius: |
| 2.0 |
| Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: |
| 0.70 |
| Tempurature Points For Resistance Readings At Zero Power: |
| 75.0 degrees celsius 7th resistance-temperature point |
| Zero Power Resistance At Specificationified Temp: |
| 210.0 ohms 4th resistance-temperature point |
| Resistance Tolerance At A Specificationified Tempurature In Percent: |
| -9.2/+9.2 9th resistance-temperature point |
| Inclosure Type: |
| Encapsulated |
| Zero Power Resistance: |
| 300.000 ohms |
| Zero Power Resistance Tolerance In Percent At Reference Temp: |
| -5.0/ + 5.0 |
| Reference Tempurature In Deg Celsius: |
| 25.0 |
| Style Designator: |
| Rod |
| Test Data Document: |
| 90073-469-508 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |

2 wire lead

NSN 5905-00-416-3522

Thermal Resistor - Page 2 of 2



| She | lf | Life: | |
|------|----|-------|--|
| Oile | •• | LIIV. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A086a0