

View Online at <https://aerobasegroup.com/nsn/5905-00-418-2452>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7495 inches and 0.7500 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Overall Length:**

2.430 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

Between 0.870 inches and 0.880 inches

**Shaft Diameter:**

Between 0.1245 inches and 0.1247 inches

**Shaft Length:**

Between 0.595 inches and 0.655 inches

**Body Length:**

1.775 inches

**Overall Diameter:**

1.065 inches

**Mounting Lip Diameter:**

Between 0.8700 inches and 0.8800 inches

**Mounting Lip Depth:**

Between 0.0570 inches and 0.0670 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3528.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.003 inches

**Shaft Radial Play:**

0.002 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

50.0 percent, rated amperes c and better finish

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.075/+0.075 2nd section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary pattern

**Function Conformity Per Section:**

2nd section independent linearity

**Fixed Tap Quantity Per Section:**

5 2nd section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 1st section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

9 oclock all primaries

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Test Data Document:**

07217-629892 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

11 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0