

View Online at <https://aerobasegroup.com/nsn/5905-00-419-3233>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Shaft Diameter:

0.125 inches

Shaft Length:

0.312 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.500 inches

Body Width:

0.781 inches

Body Height:

1.094 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.234 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

3.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Zzzy

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0