# NSN 5905-00-419-3535

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-419-3535 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Shaft Diameter:** 0.062 inches **Shaft Length:** 0.050 inches **Body Length:** Between 0.250 inches and 0.265 inches **Body Width:** Between 0.250 inches and 0.265 inches **Body Height:** Between 0.146 inches and 0.166 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 5400.0 and 10800.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section

**Actuator Travel Control Feature:** Clutch

# NSN 5905-00-419-3535

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

# **Standard Taper Curve Per Section:**

A single section

### **Test Data Document:**

95542-938-174 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0