NSN 5905-00-419-3550

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-419-3550 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.719 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 1.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.812 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 50.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

NSN 5905-00-419-3550

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0