NSN 5905-00-419-3832

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-419-3832 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.434 inches **Body Diameter:** 0.906 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.938 inches **Mounting Bushing Length:** 0.531 inches **Body Length:** 1.480 inches **Overall Diameter:** 1.078 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3168.0 **Maximum Starting Torque:** 0.70 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.375 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

32.0

Terminal Location:

Screw Thready Qty Per Inch (tpi):

Radially positioned over less than half the circumference

NSN 5905-00-419-3832

Precision Wire Wound Variable Resistor - Page 2 of 2



| Maria de la Maria de la |
|--|
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Shaft seal |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 3174.0 |
| Function Conformity Tolerance Per Section: |
| -0.003/+0.003 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0/+50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.5 free air single section |
| Function Conformity Per Section: |
| Single section absolute conformity |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| Single section table |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Test Data Document: |
| 89944-x71010030001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |