NSN 5905-00-419-7450

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-419-7450

-15.0/415.0 Electrical Resistance: 5.600 kilohms Resistance Tolerance In Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/4145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/4145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Flig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 5.600 kiohms Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Retlability Indicator: Not established Body Diameter: -0.105 inches Body Length: -0.281 inches Power Dissipation Rating In Watts: -0.281 inches Power Dissipation Rating In Watts: -0.85 let amin according to the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Demilitarization: No Flig:	
Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Retiability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 004817-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: No Demilitarization: No Demilitarization: No Filig:	Electrical Resistance:
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.080 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Demilitarization: No Emilitarization: No Effig:	5.600 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Nia Unit Of Measure: — Demilitarization: No Flig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.04-145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Filg:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.505 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-65.0/+145.0
Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Noninductive Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Reliability Indicator: Not established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reactance Characteristic:
Note established Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Noninductive
Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.281 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.105 inches
Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.281 inches
Style Designator: Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.050 free air
Test Data Document: 06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0