NSN 5905-00-420-5641

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-420-5641 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.093 inches **Body Length:** Between 0.990 inches and 1.010 inches **Body Width:** Between 0.170 inches and 0.190 inches **Body Height:** Between 0.295 inches and 0.335 inches **Actuator Type:** Flush drive with slot-hole **Fragility Factor:** Moderately rugged **Lateral Distance Between Mounting Hole Centers:** 0.750 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 2.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:**

Standard Taper Curve Per Se
A single section
Terminal Type And Quantity:
3 wire lead

NSN 5905-00-420-5641

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0