## NSN 5905-00-420-7305

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-420-7305 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.451 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0830 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 0.826 inches **Overall Diameter:** 2.203 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 

0.60 inch-ounces

Shaft End Play:

0.003 inches

## NSN 5905-00-420-7305

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Runout:  |
|--|
| 0.001 inches   |
| Lateral Runout:  |
| 0.003 inches   |
| Pilot Diameter Runout:   |
| 0.002 inches   |
| Shaft Radial Play:   |
| 0.0015 inches  |
| Fragility Factor:  |
| Rugged   |
| Terminal Location:   |
| Radially positioned over less than half the circumference  |
| Mounting Method:   |
| Clamp ring   |
| Electrical Resistance Per Section:   |
| 5.0 percent, rated amperes c and better flooring   |
| Rotary Actuator Travel In Angular Deg:   |
| 360.0  |
| Function Conformity Tolerance Per Section:   |
| -0.03/+0.03 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 125.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 4.0 7th secondary quality  |
| Function Conformity Per Section:   |
| Single section independent linearity   |
| Resistance Tolerance Per Section In Percent:   |
| -3.0/+3.0 single section   |
| Actuator Travel Control Feature:   |
| Continuous motion  |
| Function Characteristic Per Section:   |
| 7 oclock all primaries   |
|  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:   |
|  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section  Precious Material And Location:  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section  Precious Material And Location: Terminals gold   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section  Precious Material And Location: Terminals gold  Precious Material:                                   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section  Precious Material And Location: Terminals gold  Precious Material: Gold                              |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section  Precious Material And Location: Terminals gold  Precious Material: Gold  Terminal Type And Quantity: |

## NSN 5905-00-420-7305

Precision Wire Wound Variable Resistor - Page 3 of 3



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A002a0