

View Online at https://aerobasegroup.com/nsn/5905-00-420-7360

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.813 inches

Mounting Bushing Length:

0.312 inches

Body Length:

1.600 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.003 inches

Fragility Factor:

Rugged

Screw Thread Diameter:

0.375 inches



Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.20/+0.20 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

NSN 5905-00-420-7360

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

