

View Online at <https://aerobasegroup.com/nsn/5905-00-421-0768>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.625 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.2 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

156.0 single section

Rotary Actuator Travel In Angular Deg:

312.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0 to 5.5 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and +0.0 to 1.5 0 degrees celsius single section and -2.0 to 2.0 85 degrees celsius single section and +0.0 to 4.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.25 free air single section

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-3.0 to 3.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0