NSN 5905-00-421-0813

Thermal Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-421-0813

Not established Terminal Surface Treatment: Solder Terminal Length: 0.375 inches Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0 Unpackaged Unit Weight:	Deliahilita Indicator
Terminal Surface Treatment: Solder Terminal Length: 0.375 inches Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Reliability Indicator:
Solder Terminal Length: 0.375 inches Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	
Terminal Length: 0.375 inches Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	
0.375 inches Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	
Body Length: 0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	
0.043 inches Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	
Body Outside Diameter: 0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	
0.043 inches Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	0.043 inches
Terminal Diameter: 0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Body Outside Diameter:
0.004 inches Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	0.043 inches
Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Terminal Diameter:
25.0 degrees celsius Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	0.004 inches
Maximum Operating Temp: 300.0 degrees celsius Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Ambient Tempurature At Full Rated Power:
Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	25.0 degrees celsius
Thermal Time Constant In Seconds: 4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Maximum Operating Temp:
4.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	300.0 degrees celsius
Power Dissipation Constant In Milliwatts Per Deg Celsius: 0.4 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Thermal Time Constant In Seconds:
Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	4.0
Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: -4.40 Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Power Dissipation Constant In Milliwatts Per Deg Celsius:
Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	0.4
Tempurature Points For Resistance Readings At Zero Power: 90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:
90.0 degrees celsius 6th resistance-temperature point Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	-4.40
Zero Power Resistance At Specificationified Temp: 23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Tempurature Points For Resistance Readings At Zero Power:
23.5 ohms 10th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	90.0 degrees celsius 6th resistance-temperature point
Resistance Tolerance At A Specificationified Tempurature In Percent: -29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius:	Zero Power Resistance At Specificationified Temp:
-29.8/+29.8 10th resistance-temperature point Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	23.5 ohms 10th resistance-temperature point
Inclosure Type: Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Resistance Tolerance At A Specificationified Tempurature In Percent:
Encapsulated Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	-29.8/+29.8 10th resistance-temperature point
Cubic Measure: 0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Inclosure Type:
0.00005 cubic inches Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Encapsulated
Zero Power Resistance: 20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Cubic Measure:
20.000 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	0.00005 cubic inches
Zero Power Resistance Tolerance In Percent At Reference Temp: -15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	Zero Power Resistance:
-15.0/+15.0 Reference Tempurature In Deg Celsius: 25.0	20.000 kilohms
Reference Tempurature In Deg Celsius: 25.0	Zero Power Resistance Tolerance In Percent At Reference Temp:
25.0	-15.0/+15.0
25.0	Reference Tempurature In Deg Celsius:
Unpackaged Unit Weight:	25.0
	Unpackaged Unit Weight:
0.200 grams	

Style Designator:Sealed or coated bead

NSN 5905-00-421-0813

Thermal Resistor - Page 2 of 2



Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A086a0