## NSN 5905-00-421-2769

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-421-2769

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  10.0/+10.0  Electrical Resistance:  380.000 ohms  Resistance Tolerance In Percent:  0.030/+0.030  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  nclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter: |
|--|
| Electrical Resistance: 380.000 ohms Resistance Tolerance In Percent: 0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches   |
| Resistance Tolerance In Percent:  0.030/+0.030  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches   |
| Resistance Tolerance In Percent:  0.030/+0.030  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.000 inches   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  nclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  nclosure Method: Encapsulated Ferminal Type:  Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches  |
| Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  nclosure Method: Encapsulated Ferminal Type:  Wire lead Reliability Indicator: Not established Ferminal Length:  1.000 inches   |
| 55.0/+125.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches  |
| nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches  |
| Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.000 inches   |
| Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.000 inches   |
| Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.000 inches   |
| Reliability Indicator: Not established Ferminal Length: 1.000 inches   |
| Not established  Ferminal Length:  1.000 inches  |
| Terminal Length: 1.000 inches  |
| 1.000 inches   |
|  |
| Body Diameter:   |
|  |
| 0.141 inches   |
| Body Length:   |
| 0.391 inches   |
| Power Dissipation Rating In Watts:   |
| 0.100 free air   |
| Style Designator:  |
| Axial terminal each end  |
| Fest Data Document:  |
| 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)  |
| Shelf Life:  |
| N/a  |
| Jnit Of Measure:   |
| -  |
| Demilitarization:  |
| No.  |
| Filg:  |
| A001a0   |