NSN 5905-00-421-9104

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-421-9104

Electrical Resistance: 24.000 kilohms Resistance Tolerance in Percent: 0.250/40.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 30.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead 864y Length: 0.295 inches 864y Vength: 0.320 inches 864y Height: 0.100 inches Power Dissipation Rating in Watts: 0.301 inches Power Dissipation Rating in Watts: 0.302 inches 865y Power Dissipation Rating in Watts: 0.303 inches 865y Power Dissipation Rating in Watts: 0.304-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Unit of Measure: United Measure: Unite	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 24.000 kilohms Resistance Tolerance in Percent: 0.260/40.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 30.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.300 inches Body Height: 0.100 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Tests Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Lite: Wire Unit Of Measure: United Measure: Unit	
Resistance Tolerance In Percent: -0.250/4-0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: -0.00 -0.00 Ambient Tempurature In Deg Celsius At Full Rated Power: -0.00 -0	
Resistance Tolerance In Percent: -0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: -0.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 30.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 2.295 inches Body Width: 2.320 inches Body Height: 2.100 inches Power Dissipation Rating In Watts: 2.300 free air Style Designator: Terminals one edge Test Data Document: 99344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: ——Demilitarization:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 30.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 2.295 inches Body Width: 2.320 inches Body Height: 2.0100 inches Power Dissipation Rating In Watts: 2.300 free air Style Designator: Terminals one edge Test Data Document: 29344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 29349-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 29540-psfication, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.300 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.99344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2058 Shelf Life: W/A Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: -0.295 inches Body Width: -0.320 inches Body Height: -0.100 inches Power Dissipation Rating In Watts: -0.390 free air Style Designator: Terminals one edge Terst Data Document: -0.99344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	
Trempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Terst Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 10.295 inches Body Width: 10.320 inches Body Height: 10.301 inches Power Dissipation Rating In Watts: 10.300 free air Style Designator: Terminals one edge Test Data Document: 10.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.3100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	
Encapsulated Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	
Terminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization:	
Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization:	
Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Wire lead
20.295 inches Body Width: 20.320 inches Body Height: 20.100 inches Power Dissipation Rating In Watts: 20.300 free air Style Designator: Terminals one edge Test Data Document: 20.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	
Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.295 inches
Double Body Height: Double Body Height: Doubl	Body Width:
D.100 inches Power Dissipation Rating In Watts: D.300 free air Style Designator: Terminals one edge Test Data Document: D9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.320 inches
Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Height:
O.300 free air Style Designator: Terminals one edge Test Data Document: O9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.100 inches
Style Designator: Terminals one edge Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Terminals one edge Test Data Document: D9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.300 free air
Test Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
Demilitarization:	Terminals one edge
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization:	09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Filg:	Fiig:
4001a0	A001a0