## NSN 5905-00-422-0331

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-422-0331

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -500.0/+200.0  Electrical Resistance: 481.000 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0  Inclosure Method: Hermetically sealed |       |
|--|-------|
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method:  |       |
| Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0  Inclosure Method:  |       |
| -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0  Inclosure Method:   |       |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method:   |       |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0  Inclosure Method:  |       |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+150.0  Inclosure Method:  |       |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method:  |       |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method:  |       |
| -65.0/+150.0 Inclosure Method:   |       |
| Inclosure Method:  |       |
|  |       |
| Hermetically sealed  |       |
| Homotoday doubt  |       |
| Terminal Type:   |       |
| Wire lead  |       |
| Reliability Indicator:   |       |
| Not established  |       |
| Body Diameter:   |       |
| 0.250 inches   |       |
| Body Length:   |       |
| 0.750 inches   |       |
| Power Dissipation Rating In Watts:   |       |
| 0.500 free air   |       |
| Style Designator:  |       |
| Axial terminal each end  |       |
| Test Data Document:  |       |
| 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,   | etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)  |       |
| Shelf Life:  |       |
| N/a  |       |
| Unit Of Measure:   |       |
|  |       |
| Demilitarization:  |       |
| No   |       |
| Fiig:  |       |
| A001a0   |       |