## NSN 5905-00-422-1450

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-422-1450 **Section Quantity:** 1 **Body Style:** Cylindrical friction mounted **Reliability Indicator:** Not established **Body Diameter:** 1.825 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.620 inches **Body Length:** 4.000 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 1.30 inch-ounces **Maximum Running Torque:** 0.90 inch-ounces **Maximum Stop Torque:** 100.00 inch-ounces **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Flange **Electrical Resistance Per Section:** 10.0 kilohms single section Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 3600.0 single section **Rotary Actuator Travel In Angular Deg:** 7210.0 **Function Conformity Tolerance Per Section:** -0.40/+0.40 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** 

Single section absolute linearity **Fixed Tap Quantity Per Section:** 2 single section

## NSN 5905-00-422-1450

Precision Wire Wound Variable Resistor - Page 2 of 2



## **Tap Location Tolerance Per Section:**

-0.5/+0.5 degrees angular rotation single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

**Function Characteristic Per Section:** 

Single section linear

**Terminal Type And Quantity:** 

5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0