## NSN 5905-00-422-3845

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-422-3845

Electrical Resistance: 79.900 kilohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Resistance Tolerance In Percent:  0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0  Inclosure Method: Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter:
Resistance Tolerance In Percent:  0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  nclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Incapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Encapsulated  Ferminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
0.001  Body Diameter:
Body Diameter:
).125 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0