

View Online at https://aerobasegroup.com/nsn/5905-00-425-3503

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-15.0/+15.0

#### **Electrical Resistance:**

22.600 ohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0/+145.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

#### . . . . . . . . .

Reliability Indicator:

## Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### Body Diameter:

0.250 inches

#### **Body Length:**

0.500 inches

#### **Power Dissipation Rating In Watts:**

0.150 free air

#### Cubic Measure (non-core):

0.025 cubic inches

#### Unpackaged Unit Weight:

2.000 grams

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-39005/4 government specification

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5905-00-425-3503

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig: A001a0