NSN 5905-00-425-6001

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-425-6001

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.125 inches
Body Length:
0.750 inches
Body Width:
0.250 inches
Body Height:
0.190 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.600 inches
Terminal Location:
Dual inline
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.600 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-425-6001

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
2 slider terminals
Terminal Type And Quantity:
4 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0