## NSN 5905-00-425-8283

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-425-8283 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Terminal Length:** Between 0.177 inches and 0.197 inches **Mounting Hole Diameter:** 0.074 inches **Mounting Slot Width:** 0.074 inches **Shaft Diameter:** Between 0.055 inches and 0.065 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.145 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity: Center To Center Distance Between Terminal Rows:** 

**Terminal Location:** Right adjacent side two rows **Mounting Method:** Slot and unthreaded hole 0.100 inches **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.0 ohms single section

## NSN 5905-00-425-8283

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



0.100 inches

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

27489-6211-4075-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0