

View Online at <https://aerobasegroup.com/nsn/5905-00-426-8862>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.550 inches

Overall Height:

0.508 inches

Overall Width:

0.257 inches

Shaft Diameter:

0.110 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.300 inches

Body Width:

0.257 inches

Body Height:

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

8.00 inch-ounces

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

0.125 inches

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7920.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0