## NSN 5905-00-426-8863

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-426-8863 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.550 inches **Overall Height:** 0.508 inches **Overall Width:** 0.257 inches **Shaft Diameter:** 0.110 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.300 inches **Body Width:** 0.257 inches **Body Height:** 0.320 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Maximum Starting Torque:** 8.00 inch-ounces **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** 

Unf

Screw Thready Qty Per Inch (tpi):

28.0

**Terminal Location:** 

Lower adjacent side two rows

**Mounting Method:** 

Standard bushing

NSN 5905-00-426-8863 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.125 inches
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0