Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-427-1080

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.250 inches

#### Terminal Length:

0.187 inches

Body Diameter:

0.750 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.375 inches

#### **Body Length:**

0.375 inches

# **Overall Diameter:**

0.937 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Maximum Running Torque:

6.00 inch-ounces

# Maximum Stop Torque:

80.00 inch-ounces

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.375 inches

# Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# NSN 5905-00-427-1080

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



# **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 250.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** -3.0 to 0.0 -55 degrees celsius single section and -5.0 to 3.0 25 degrees celsius single section and -0.0 to 3.0 85 degrees celsius single section and -5.0 to 10.0 25 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** Any acceptable **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-milr94a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0