## NSN 5905-00-428-9818

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-428-9818

| view Online at https://aerobasegroup.com/hist//3303-00-420-3010  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -10.0/+10.0  |
| Electrical Resistance:   |
| 50.500 kilohms   |
| Resistance Tolerance In Percent:   |
| -0.050/+0.050  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reactance Characteristic:  |
| Noninductive   |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Body Diameter:   |
| 0.250 inches   |
| Body Length:   |
| 0.750 inches   |
| Power Dissipation Rating In Watts:   |
| 0.250 free air   |
| Cubic Measure (non-core):  |
| 0.037 cubic inches   |
| Unpackaged Unit Weight:  |
| 2.500 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39005/3 government specification   |
| Shelf Life:  |
| N/a  |

--

**Unit Of Measure:** 

## NSN 5905-00-428-9818

Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0