

View Online at <https://aerobasegroup.com/nsn/5905-00-430-2923>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.047 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round

Switch Type:

Push-pull

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Double pole single throw normally open and double pole single throw normally closed

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Upper and lower adjacent side from adjustment control

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

2.0 kilohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

2.000 ac

Standard Taper Curve Per Section:

A single section

Test Data Document:

93346-3450867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0